

The safety data sheet is in accordance with Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

# SECTION 1: Identification of the substance / mixture and of the company / undertaking

Date issued	11.12.2012
Revision date	13.01.2020

# 1.1. Product identifier

Product name	FRESH FACTORY MIXED CONCRETE
Synonyms	Factory mixed concrete in strength classes B10 to B95 according to EN 206-1 for concrete structures in the durability classes M90, M60, M45, MF45, M40, MF40.

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Product group	Concrete.
Use of the substance / preparation	Concrete constructions.
Relevant identified uses	SU19 Building and construction work

# 1.3. Details of the supplier of the safety data sheet

Company name	Unicon AS
Office address	Tevlingveien 23
Postal address	Tevlingveien 23
Postcode	1081
City	Oslo
Country	NORWAY
Telephone number	+47 959 90 970
Email	Johnny.Madsen@unicon.no
Website	http://www.unicon.no
Enterprise No.	942 822 979
Contact person	Johnny Madsen

# 1.4. Emergency telephone number

# Emergency telephoneTelephone number: +47 22 59 13 00

Description: Norwegian Poison Information Center

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

	lassification according to egulation (EC) No 1272/2008	Skin Irrit. 2; H315
	CLP / GHS]	Eye Dam. 1; H318
-	ubstance / mixture hazardous roperties	Causes skin irritation. Causes serious eye damage.
	dditional information on lassification	The mixture is not classified as STOT SE 3; H335: May cause respiratory irritation, because wet concrete does not dust. Classification based on extreme pH is not relevant. Only one component classified as corrosive is present in the mixture. The mixture should not have a classification that is stricter than the substance's own classification.

# 2.2. Label elements

Hazard pictograms (CLP)		
Signal word	Danger	
Hazard statements	H315 Causes skin irritation. H318 Causes serious eye damage.	
Precautionary statements	<ul> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P280 Wear protective gloves / protective clothing / eye protection / face protection.</li> <li>P302+P352 IF ON SKIN: Wash with plenty of soap and water.</li> <li>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P310 Immediately call a POISON CENTER or doctor / physician.</li> </ul>	

# 2.3. Other hazards

PBT / vPvB

Not PBT / vPvB.

# **SECTION 3: Composition / information on ingredients**

# 3.2. Mixtures

Substance	Identification	Classification	Contents	Notes
Portland Cement, chromium reduction	CAS No.: 65997-15-1 EC No.: 266-043-4	STOT SE3;H335 Skin Irrit. 2;H315 Eye Dam. 1;H318 Skin Sens. 1; H317	10 - 20 %	
Ash (resid) , coal	EC No.: 931-322-8 REACH Reg. No.:		0 - 10 %	2

	01-2119491179-27		
fumes, silica	CAS No.: 69012-64-2	0 - 2 %	6
	EC No.: 273-761-1		
	REACH Reg. No.:		
	01-2119486866-17-0000		

<sup>2</sup>Substance with a workplace exposure limit <sup>6</sup>Substance listed as additional information

Description of the mixture Construction materials on basis of minerals. Contains water and aggregation	103.
Substance comments       When additives are added at the construction site, a SDS for this/these mexist.         The portland cement contains max 2 mg water soluble chromates pr. kg. cement.         Portland Cement Clinker (CAS nr. 65997-15-1) is except the requirement for REACH registration.         See section 16 for explanation of hazard statements (H) listed above.	dry

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

General	Emergency telephone number: see section 1.4. In case of unconsciousness or severe accidents, call 113.
Inhalation	Not relevant. Fresh air and rest.
Skin contact	Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Flush immediately with plenty of water. Remove contact lenses and open eyes wide apart. Continue to rinse for 30 minutes. By prolonged rinsing, use luke warm water to avoid damage to the eye. Immediately consult a doctor. Transport to physician. Keep on flushing during transport.
Ingestion	Rinse mouth thoroughly. Drink a few glasses of water or milk. Never give liquid to an unconscious person. Do not induce vomiting. Get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Acute symptoms and effects	Skin contact: The chemical irritates the skin and can cause itching, burning and
	redness.
	Eye contact: Causes severe burns and serious eye damage.
Delayed symptoms and effects	Same as the acute symptoms.

### 4.3. Indication of any immediate medical attention and special treatment needed

Other information

Treat symptomatically. No specific information from the manufacturer.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

#### 5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards	The chemical is not classified as flammable. The chemical is non-combustible. None hazardous combustion products are expected.
5.3. Advice for firefighters	
Personal protective equipment	Use compressed air equipment when the chemical is involved in fire. In case of evacuation, an approved protection mask should be used. See also section 8.

Containers close to fire should be removed immediately or cooled with water.

SECTION 6: Accidental release measures	
SECTION 6' Acadoptal ralazea mazeurae	
JAEG HUN D. ACCIDEIILAI I EIEASE IIIEASUIES	

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal protection measures	Use protective equipment as referred to in section 8.
------------------------------	---

#### 6.2. Environmental precautions

Environmental precautionary	Do not allow to enter into sewer, water system or soil.
measures	

#### 6.3. Methods and material for containment and cleaning up

Clean up	Use mechanical handling equipment. Collect in suitable containers and deliver as waste according to section 13.
	Small quantities are dissolved or diluted with water and flushed to a collection basin.

### 6.4. Reference to other sections

Other instructions

Other information

See also sections 8 and 13.

# SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Handling	Arrange working conditions to avoid direct contact.
	Use protective equipment as referred to in section 8.

### Protective safety measures

Advice on general occupational	Do not eat, drink or smoke during work. Wash hands at the end of each work shift
hygiene	and before eating, smoking and using the toilet. Wash contaminated clothing
	before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage	Not to be stored.
	Keep out of reach of children.

#### 7.3. Specific end use(s)

Specific	use(s)
----------	--------

See section 1.2.

# SECTION 8: Exposure controls / personal protection

# 8.1. Control parameters

Substance Id	entification	Exposure limits	TWA Year
Ash (resid) , coal		Limit value (8 h) : 4 mg/m <sup>3</sup> Comments: Coal dust - Total dust.	
		Limit value (8 h) : 1,5 mg/ m³ Comments: Coal dust - Respirable dust.	
Control parameters comments	References (laws/regulations): Norwegian regulation on exposure limits: FOR 2011-12-06 nr 1358 Forskrift om tiltaks- og grenseverdier (sist endret gjennom FOR-2018-12-20-2186).		

# 8.2. Exposure controls

# Precautionary measures to prevent exposure

Technical measures to prevent exposure	Provide adequate ventilation. The personal protective equipment must be CE-marked and the latest version of the standards shall be used. The protective equipment and the specified standards recommended below are only suggestions, and should be selected on advice from the supplier of such
	equipment. A risk assessment of the work place/work activities (the actual risk) may lead to other control measures. The protection equipment's suitability and durability will depend on application.

# Eye / face protection

Eye protection equipment	Description: Wear tight-fitting goggles or face shield. Reference to relevant standard: EN 166 (Personal eye-protection. Specifications).
Additional eye protection measures	Eye wash facilities shall be available at the work place. Either a fixed eye wash facility connected to the drinking water (preferably warm water) or a portable disposable unit.

# Hand protection

Suitable materials	Nitrile. Rubber, neoprene or PVC.
Breakthrough time	Value: > 8 hour(s) Comments: Other types of gloves may be recommended by the glove supplier.
Thickness of glove material	Comments: Not specified by the manufacturer.
Hand protection equipment	Description: Use chemical resistant gloves. Glove thickness must be chosen in consultation with the glove supplier, who can inform about the breakthrough time for the glove. The gloves abilities may vary among the different glove manufacturers. Reference to relevant standard: BS-EN 374 (Protective gloves against chemicals and micro-organisms). BS-EN 420 (Protective gloves. General requirements and test methods).

#### Skin protection

Recommended protective clothing	Description: Wear appropriate protective clothing to protect against possible skin contact. Wear boots (pants on top of boots).
Additional skin protection measures	Emergency shower should be available at the workplace.

# **Respiratory protection**

Recommended respiratory	Description: Normally not required.
protection	

## Appropriate environmental exposure control

Environmental exposure controls

ols Do not allow to enter into sewer, water system or soil.

# SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state	Liquid to pasty, dependent on water content.
Colour	Gray. May be pigmented.
Odour	Characteristic.
Odour limit	Comments: Not known.
рН	Status: In aqueous solution Value: ~ 12
Melting point / melting range	Value: ~ 0 °C
Boiling point / boiling range	Value: ~ 100 °C
Flash point	Comments: Not combustible.
Evaporation rate	Comments: Not known.
Flammability (solid, gas)	Not relevant, see flash point.
Explosion limit	Comments: Not known.
Vapour pressure	Comments: Not relevant.
Vapour density	Comments: Not relevant.
Relative density	Value: ~ 2400 kg/m3
Bulk density	Comments: Not known.
Solubility	Medium: Water Comments: Completely soluble in water.
Partition coefficient: n-octanol/ water	Comments: Not known.
Spontaneous combustability	Comments: Not relevant.
Decomposition temperature	Comments: Does not decompose.
Viscosity	Comments: Varies.
Explosive properties	Not explosive.

**Oxidising properties** 

Not oxidizing.

### 9.2. Other information

#### Other physical and chemical properties

Comments

No further information is available.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reactivity

No reactivity hazards.

#### 10.2. Chemical stability

Stability

Stable under normal temperature conditions and recommended use.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No hazardous reactions known.

### 10.4. Conditions to avoid

Conditions to avoid	None known.

## 10.5. Incompatible materials

Materials to avoid

None expected.

### **10.6. Hazardous decomposition products**

Hazardous decomposition	No hazardous decomposition products.
products	

# **SECTION** 11: Toxicological information

### 11.1. Information on toxicological effects

Other toxicological data There are no health hazard due to cured chemical.

# Other information regarding health hazards

Assessment of acute toxicity, classification	Based on available data, the classification criteria are not met.
Assessment of skin corrosion / irritation, classification	Irritating to skin.
Assessment of eye damage or irritation, classification	Causes serious eye damage.
Assessment of respiratory sensitisation, classification	Based on available data, the classification criteria are not met.
Assessment of skin sensitisation, classification	Based on available data, the classification criteria are not met. The cement used is chrome reduced to prevent sensitation.

Assessment of germ cell mutagenicity, classification	Based on available data, the classification criteria are not met.
Assessment of carcinogenicity, classification	Based on available data, the classification criteria are not met.
Assessment of reproductive toxicity, classification	Based on available data, the classification criteria are not met.
Assessment of specific target organ toxicity - single exposure, classification	Based on available data, the classification criteria are not met.
Assessment of specific target organ toxicity - repeated exposure, classification	Based on available data, the classification criteria are not met.
Assessment of aspiration hazard, classification	Based on available data, the classification criteria are not met.

## Symptoms of exposure

In case of ingestion	Unlikely because of the chemical condition. The product causes irritation of mucous membranes and may cause abdominal discomfort if swallowed.
In case of skin contact	The chemical irritates the skin and can cause itching, burning and redness. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Langvarig eller gjentatt påvirkning kan forårsake irritasjon/svie og sårskader.
In case of inhalation	When mixing cement to concrete: Dust may irritate respiratory system.
In case of eye contact	Risk of serious damage to eyes.

# SECTION 12: Ecological information

# 12.1. Toxicity

Ecotoxicity The chemical is not classified as harmful to the environment.

# 12.2. Persistence and degradability

Persistence and degradability	The product reacts with water to form a solid insoluble reaction product which is
description/evaluation	non-degradable, according to information available.

# 12.3. Bioaccumulative potential

Bioaccumulation, evaluation Not expected to bioaccumulate.

### 12.4. Mobility in soil

# 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB	Not PBT / vPvB
assessment	

#### 12.6. Other adverse effects

Additional ecological information	Alkalies cause increased pH values in the water. A high pH value harms aquatic
-----------------------------------	--

organisms.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Appropriate methods of disposal for the chemical EWC waste code	Dispose of waste in local landfill. EWC waste code: 170101 concrete
	Classified as hazardous waste: No
Other information	Do not empty into drains.

SECTION 14: Transport information		
Dangerous goods	No	
14.1. UN number		
Comments	Not relevant.	
14.2. UN proper shipping na	ame	
Comments	Not relevant.	
4.3. Transport hazard class(es)		
Comments	Not relevant.	
14.4. Packing group		
Comments	Not relevant.	
14.5. Environmental hazard	S	
IMDG Marine pollutant	No	
14.6. Special precautions for	or user	
Special safety precautions for user	Not relevant.	

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Transport in bulk (yes/no)

No

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

References (laws/regulations)Regulation (EC) No 1272/2008 on classification, labelling and packaging of<br/>substances and mixtures (CLP-regulation) with later amendments.<br/>Regulation (EC) No 1907/2006 on the registration, evaluation, authorization and<br/>restriction of chemicals (REACH Regulation), with later amendments.

	The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895). Dangerous Goods regulations
Comments	Fresh Factory Mixed Concrete are covered by paragraph 47, and its use is restricted according to REACH Annex XVII. This mixture does not meet the criteria for the restriction.
Declaration No.	80891

# 15.2. Chemical safety assessment

Chemical safety assessment	No
performed	
CSR required	No

SECTION 16: Other information		
Supplier's notes	The information contained in this SDS must be made available to all those who handle the product.	
List of relevant H-phrases (Section 2 and 3)	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.	
Key literature references and sources for data	Common template designed for the members of FABEKO.	
Abbreviations and acronyms used	<ul> <li>ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road</li> <li>RID: The Regulations concerning the International Carriage of Dangerous Goods by Rail</li> <li>IMDG: The International Maritime Dangerous Goods Code</li> <li>IATA: The International Air Transport Association</li> <li>IBC: Intermediate Bulk Container.</li> <li>ICAO: The International Civil Aviation Organisation</li> <li>MARPOL 73/78 is the International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("MARPOL" is short for marine pollution and 73/78 short for the years 1973 and 1978.)</li> <li>PBT: Persistent, Bioaccumulative and Toxic</li> <li>vPvB: very Persistent and very Bioaccumulative</li> </ul>	
Information added, deleted or revised	Sections being revised since previous version: 1-4, 6, 8-9, 11-16	
Checking quality of information	This SDS is quality controlled by Kiwa Teknologisk Institutt in Norway, certified according to the Quality Management System requirements specified in ISO 9001:2015.	
Version	3	
Prepared by	Kiwa Teknologisk Institutt, Norway by Sissel Rogstad	